



## Overview

Model Name	Rack PDU, Basic, Zero U, 16A, 208/230V, (15) C13
Includes	Rack Mounting brackets
Standard Lead Time	Usually in Stock
Product Distribution	Afghanistan

## Output

Nominal Output Voltage	200V
Maximum Total Current Draw per Phase	16 A
Output Connections	(15) IEC 320 C13 (Battery Backup)

## Input

Nominal Input Voltage	200V
Input Frequency	50/60 Hz
Input Connections	IEC-320 C20
Cord Length	2.5 meters
Number of Power Cords	1
Maximum Line Current per phase	16 A
Maximum Input Current per phase	16 A
Load Capacity	3680 VA

## Physical

Net Weight	2.0 kg
Maximum Height	620.0 mm
Maximum Width	44.0 mm
Maximum Depth	44.0 mm
Shipping Weight	2.73 kg
Shipping Height	638.0 mm
Shipping Width	168.0 mm
Shipping Depth	146.0 mm
Color	Black

## Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-15000 meters

## Conformance

Approvals	CE
Standard warranty	2 years repair or replace

## Sustainable Offer Status

RoHS	Compliant
Other Environmental Compliance	China RoHS