

FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

blue, RJ45-RJ45 connector, 10 m

CORNING

The application-neutral FutureCom™ category 6_A patch cords have four individual foil-shielded pairs (PiMF) and an additional braid shield (S/FTP). They are assembled with a shielded RJ45 connectors on each end.

The zero halogen patch cords (LSZH) are non-corrosive according to IEC 60754-2 (FRNC) and EN 50267, low smoke according to IEC 61034 and EN 50268 and flame retardant according to IEC 60332-1, Category B and EN 50266-2-1. FutureCom™ S500 patch cords provide additional latch protection.

They are available in various lengths and colours.

Features

- S/FTP flex cable, Category 7
- Application-neutral due to using all four pairs of RJ45 connectors
- Minimum surface transfer impedance of cable (<10 mΩ/m at 10 MHz)
- Outstanding transmission characteristics according to 10GBase-T
- Additional latch protection
- Category 6_A
- PVP Certificate



Specifications

General Specifications

Cable assembly type	Patch Cords
Environment	Indoor
Cable type	S/FTP
Halogen-free	Yes
Category	6 _A
Product category	Core product

Temperature Range

Operation	-20 °C to 60 °C
-----------	-----------------

FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

blue, RJ45-RJ45 connector, 10 m

CORNING

Design - Connector A

Connector Type	RJ45 - 8/8
----------------	------------

Mechanical Specifications - Connector A

Durability	750 Cycles
------------	------------

Electrical Specifications - Connector

Insulation Resistance	≥ 5000 MΩ
-----------------------	-----------

Design - Connector B

Connector Type	RJ45 - 8/8
----------------	------------

Mechanical Specifications - Connector B

Durability	750 Cycles
------------	------------

Cable design

Min. Bend Radius Installation	40 mm
Min. Bend Radius Operation	30 mm
Outer diameter	5.8 mm
Outer jacket material	LSZH™/FRNC
Outer jacket colour	blue

Mechanical Characteristics

Conductor Insulation	Braided shield Individual pair shield (PiMF)
----------------------	--

Electrical characteristics (at 20°C)

Max. loop resistance	290 Ω/km
DC resistance unbalance	2 %
Impedance Z_0 at 0-100 MHz	100 Ω +- 15%
Impedance Z_0 at 101-250 MHz	100 Ω +- 18%

FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector

blue, RJ45-RJ45 connector, 10 m

CORNING

Electrical characteristics (at 20°C)

Impedance z_0 at 251-600 MHz	100 Ω +/- 25%
Surface transfer impedance	< 10 m Ω /m per meter at 10 MHz
Mutual capacity	43 pF/m
Earth coupling at 0.001 MHz	1600
Propagation delay \geq 10 MHz	4.3 ns/m
Delay skew	20 ns/100 m

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Ordering Information

Part Number	CCAAGB-G2002-A100-C0
Product Description	FutureCom™ EA Patch Cord, FRNC, RJ45 - RJ45 connector, blue, 10 m
EAN Code	4042673311812
Weight	0.48 kg
Length	10 m

Shipping Information

Units Per Delivery	1/1
--------------------	-----



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2016 Corning Optical Communications. All rights reserved.